



ESTIMATED GROSS SHIPPING WEIGHT = 39 LBS

SPECIFICATIONS:
 ALL MOLDED BUMPER HAVE PRE-DRILLED, COUNTERSUNK MOUNTING HOLES FOR EASY INSTALLATION, SIZED TO ACCEPT Ø3/4" ANCHOR.

- REINFORCED PRIME RUBBER; HARDNESS 70±5 (ASTM D2240)
- 95% IMPACT RECOVERY
- 8.3 N/MM2 (±10%) TENSILE STRENGTH (ASTM D792)
- 1.2 G/CM3 (±0.1) DENSITY (ASTM D412C)

ALL DIMENSIONS ARE ± 1/4" UNLESS SPECIFIED OTHERWISE

DRAWN BY: **S.SARGESON** DATE:
 CHECKED BY: DATE:

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF IDEAL WAREHOUSE INNOVATIONS INC. ANY REPRODUCTION IN PART OR AS A WHOLE IS PROHIBITED.

3rd Angle	SIZE: A		
	DESCRIPTION: MOLDED RUBBER BUMPER T		
SCALE: 1:8	SHEETS: 1 of 1	DRAWING NUMBER: MKT_T	REV: 1