


SlowStop® Rebounding Bollard – 6” (60-5203)



Color: RAL 1023 Safety Yellow Bollard
RAL 9005 Black Base

Diameter: 6.63" [168.4 mm] (6" ANSI Schedule 40)
Height: 42" [1067mm]

Set Screws: 8 M16 x 2.00
8mm Hex

Cap: Black Plastic

Installs with eight (8) 5/8" x 5-1/2"
Concrete Screw Anchors

MASS (LBS)	5000	7500	10000	15000	20000	25000	30000	40000	80000
SPEED (MPH)									
1.0	Green	Green	Green	Green	Green	Green	Green	Green	Green
1.5	Green	Green	Green	Green	Green	Green	Green	Green	Green
2.0	Green	Green	Green	Green	Green	Green	Green	Green	Yellow
2.5	Green	Green	Green	Green	Green	Green	Green	Green	Yellow
3.0	Green	Green	Green	Green	Green	Green	Green	Yellow	Red
3.5	Green	Green	Green	Green	Green	Green	Yellow	Red	Red
4.0	Green	Green	Green	Green	Yellow	Yellow	Yellow	Red	Red
4.5	Green	Green	Green	Yellow	Yellow	Yellow	Red	Red	Red
5.0	Green	Green	Yellow	Yellow	Red	Red	Red	Red	Red
5.5	Green	Yellow	Yellow	Red	Red	Red	Red	Red	Red
6.0	Green	Yellow	Yellow	Red	Red	Red	Red	Red	Red
6.5	Green	Yellow	Yellow	Red	Red	Red	Red	Red	Red
7.0	Green	Yellow	Yellow	Red	Red	Red	Red	Red	Red

No Damage / Negligible Damage
Will Stop / Potential Damage to Guard
Guard is under-sized

SPECIFICATIONS

- Stopping Power: 25,868 joules / 19,072 ft-lb.
- No Damage Rating: 12,934 joules / 9,536 ft-lb.
- Temperature Rating: -40°C/°F
- Pipe Coating: 60µm Hot Dipped Galvanized + 60µm Polyester Outdoor Powder Coat
- Cast Iron Coating: Environmentally Friendly Water-Based KTL Coating plus Powder Coat C5I Rated.

RECOMMENDED USES

- Heavy Duty
- Loading Docks and Warehouse Entrance Ramps
- Equipment and Storage Rack Guarding
- Utility Protection
- Pedestrian Safety
- Access Denial
- Post-tensioned Concrete
- Not for K-Rated Security Use



Toll-Free Phone: **1-866-828-6737**
Toll-Free Fax: **1-844-899-0088**
idealwarehouse.com info@idealwarehouse.com